

rooms for each of the following operations depending upon the various types of operations conducted, but, in no case, shall the receiving or holding of live rabbits or killing operations be permitted in rooms in which eviscerating operations are performed:

(1) The receiving and feeding of live rabbits.

(2) Killing and skinning operations.

(3) Eviscerating, chilling, and packing operations for ready-to-cook rabbits.

(4) Inedible products departments.

(5) Refuse room.

(b) Rooms for holding carcasses for further inspection. Rooms and compartments in which carcasses or parts thereof are held for further inspection shall be in such number and such location as the needs of the inspection in the plant may require. They shall be equipped with locks and keys and the keys shall not leave the custody of the inspector in charge of the plant. All such rooms and compartments shall be marked conspicuously with the word "retained" in letters not less than 2 inches high.

(c) Coolers and freezers. Coolers and freezers of adequate size and capacity shall be provided to reduce the internal temperature of ready-to-cook rabbits prepared and otherwise handled in the plant to 36 °F. within 24 hours unless other cooling facilities are available.

(d) Refuse rooms. Refuse rooms shall be entirely separate from other rooms in the plant, and shall have tight fitting doors and be properly ventilated.

(e) Storage and supply rooms. The storage and supply rooms shall be in good repair, kept dry, and maintained in a sanitary condition.

(f) Boiler room. The boiler room shall be a separate room, if necessary, to prevent its being a source of dirt and objectionable odors entering any room where ready-to-cook rabbits are prepared, processed, handled, and stored.

(g) Inspector's office. Furnished office space, including, but not being limited to, light, heat, and janitor service shall be provided rent free in the official plant for the exclusive use for official purposes of the inspector and the Administration. The room or rooms set apart for this purpose must meet with the approval of the regional

supervisor and be conveniently located, properly ventilated, and provided with lockers or cabinets suitable for the protection and storage of supplies and with facilities suitable for inspectors to change clothing.

(h) Toilet rooms. Toilet rooms opening directly into rooms where rabbit products are exposed shall have self-closing doors and shall be ventilated to the outside of the building.

§ 354.222 Floors, walls, ceilings, etc.

(a) Floors. All floors in rooms where exposed products are prepared or handled shall be constructed of or finished with materials impervious to moisture, so they can be readily and thoroughly cleaned. The floors in killing, ice cooling, ice packing, eviscerating, cooking, boning, and cannery rooms shall be graded for complete runoff with no standing water.

(b) Walls, posts, partitions, doors. All walls, posts, partitions, and doors in rooms where exposed products are prepared or handled shall be smooth and constructed of materials impervious to moisture to a height of 6 feet above the floor to enable thorough cleaning. All surfaces above this height must be smooth and finished with moisture-resistant material.

(c) Ceilings. Ceilings must be moisture-resistant in rooms where exposed products are prepared or handled, and finished and sealed to prevent collection of dirt or dust that might sift through flooring above or fall from collecting surfaces on equipment or exposed product.

§ 354.223 Drainage and plumbing.

There shall be an efficient drainage and plumbing system for the plant and premises.

(a) Drains and gutters. All drains and gutters shall be properly installed with approved traps and vents. The drainage and plumbing system must permit the quick runoff of all water from plant buildings, and surface water around the plant and on the premises, and all such water shall be disposed of in such a manner as to prevent a nuisance or health hazard.

(b) Sewage and plant wastes. (1) The sewerage system shall have adequate slope and capacity to remove readily